

ENGINE SPECIFICATIONS

	Diesel 150	Diesel 190	Petrol
Capacity	2 179 cm ³	2179 cm ³	1999 cm ³
Firing order	1-3-4-2	1-3-4-2	1-3-4-2
Compression ratio	15.8:1	15.8:1	10:1
Maximum torque	420 Nm at 1750 rpm	420 Nm at 1750 rpm	317 Nm at 3200 rpm
Number of cylinders	4	4	4
Power output	110 kW (150 PS) at 4000 rpm	140 kW (190 PS) at 3500 rpm	177W (240 PS) at 5500 rpm

LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	Petrol vehicles 2.0L	SAE 5W-30 meeting Ford 913-B specification.
	Diesel vehicles 2.2L (with DPF)	SAE 5W-30 meeting Ford 934-B specification.
	Diesel vehicles 2.2L (without DPF)	SAE 5W-30 meeting Ford 913-B or 913-C specification.
Main gearbox oil	Manual transmission	Castrol BOT 350 M3
Main gearbox oil	Automatic transmission	Nippon AW-1
Power Transfer unit	All vehicles	Castrol BOT 118
Haldex coupling	All vehicles	STAT OIL SL01-301
Rear differential oil	All vehicles	Castrol EPX
Power steering fluid	All vehicles	Pentosin CHF202
Brake/Clutch fluid	All vehicles	Shell DOT4 ESL. If unavailable, a low viscosity synthetic compatible DOT4 brake fluid that meets ISO 4925 class 6 and Land Rover LRES22BF03 requirements may be used.
Screen washer	All vehicles	Screen wash with frost protection
Coolant	All vehicles	1:1 mixture of Castrol SF antifreeze and water.