

LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	Petrol vehicles 2.0L	SAE 5W-30 engine oil meeting specification WSS-M2C913-C or B.
	Diesel vehicles 2.2L (with DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable 5W-30 engine oils to ACEA C2 specification may be used.
	Diesel vehicles 2.2L (without DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C913- C or B. If unavailable 5W-30 engine oils to ACEA A5/B5 specification may be used.
Main gearbox oil	Manual transmission	Castrol BOT 350 M3
Main gearbox oil	Automatic transmission	Nippon AW-1
Power Transfer unit	All vehicles	Castrol BOT 118
Haldex coupling	All vehicles	STAT OIL SL01-301
Rear differential oil	All vehicles	Castrol EPX
Power steering fluid	All vehicles	Pentosin CHF202
Brake fluid	All vehicles	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Screen wash	All vehicles	Screen wash with frost protection
Screen cleaning paste	All vehicles	Land Rover screen cleaning paste DNJ500340
Coolant	All vehicles	1:1 mixture of Castrol SF antifreeze and water

Land Rover recommends Castrol EDGE Professional:

