

## LUBRICANTS AND FLUIDS

Part	Variant	Specification
<b>Engine oil</b>	Diesel vehicles with a Diesel Particulate Filter (DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable, 5W-30 engine oils to ACEA C2 specification may be used.
	Diesel vehicles without a DPF	SAE 5W-30 engine oil meeting specification WSS-M2C913-C. If unavailable, 5W-30 engine oils to ACEA A5/B5 specification may be used.
	V6 Petrol vehicles	SAE 5W-20 engine oil meeting specification WSS-M2C925-A. If unavailable or, where ambient temperatures fall to lower than -20° C, SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122 should be used.
	V8 Petrol vehicles	SAE 5W-20 engine oil meeting specification WSS-M2C925-A.
<b>Transmission oil</b>	All transmissions	Land Rover recommends Shell ATF L12108
<b>Transfer gearbox oil</b>	Without low range transmission	Land Rover recommends Castrol BOT 850
	With low range transmission	Land Rover recommends TL 7300 Shell TF 0753
<b>Front differential oil</b>	All vehicles	Land Rover recommends Castrol SAF-XO
<b>Rear differential oil</b>	Non-locking	Land Rover recommends Castrol SAF-XO
<b>Rear differential oil</b>	Electronic locking	Land Rover recommends Castrol BOT 720
<b>Dynamic response fluid</b>	V6 Diesel and V8 Petrol	Land Rover recommends Texaco Cold Climate PAS fluid 33270 is recommended.

<b>Part</b>	<b>Variant</b>	<b>Specification</b>
<b>Brake fluid</b>	All vehicles	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
<b>Screen washer</b>	All vehicles	Screen wash with frost protection
<b>Coolant</b>	All vehicles	Land Rover recommends a 1:1 mixture of Havoline XLC antifreeze and water.

Jaguar Land Rover recommends Castrol oils.

