

LUBRICANTS AND FLUIDS

| Part | Variant | Specification |
|-------------------------------|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine oil | Diesel vehicles with a Diesel Particulate Filter (DPF) | SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable, 5W-30 engine oils to ACEA C2 specification may be used. |
| | Diesel vehicles without a DPF | SAE 5W-30 engine oil meeting specification WSS-M2C913-C. If unavailable, 5W-30 engine oils to ACEA A5/B5 specification may be used. |
| | V6 Petrol vehicles | SAE 5W-20 engine oil meeting specification WSS-M2C925-A. If unavailable or, where ambient temperatures fall to lower than -20° C, SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122 should be used. |
| | V8 Petrol vehicles | SAE 5W-20 engine oil meeting specification WSS-M2C925-A. |
| Transmission oil | All transmissions | Land Rover recommends Shell ATF L12108 |
| Transfer gearbox oil | Without low range transmission | Land Rover recommends Castrol BOT 850 |
| | With low range transmission | Land Rover recommends TL 7300 Shell TF 0753 |
| Front differential oil | All vehicles | Land Rover recommends Castrol SAF-XO |
| Rear differential oil | Non-locking | Land Rover recommends Castrol SAF-XO |
| Rear differential oil | Electronic locking | Land Rover recommends Castrol BOT 720 |
| Dynamic response fluid | V6 Diesel and V8 Petrol | Land Rover recommends Texaco Cold Climate PAS fluid 33270 is recommended. |

| Part | Variant | Specification |
|----------------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Brake fluid | All vehicles | Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used. |
| Screen washer | All vehicles | Screen wash with frost protection |
| Coolant | All vehicles | Land Rover recommends a 1:1 mixture of Havoline XLC antifreeze and water. |

Jaguar Land Rover recommends Castrol oils.

