

Wheels and tyres

APPROVED WINTER TYRES

18 inch wheels 235/65 R18 110H Dunlop Winter Sport M3.
19 inch wheels 255/55 R19 111H Goodyear Ultra Grip.
20 inch wheels 255/50 R20 109H Continental Cross Contact Winter

Winter tyre pressures

The cold tyre inflation pressures for winter tyres are the same as those for normal tyres of the same size.

USING SNOW CHAINS

WARNINGS



Only use traction devices in heavy snow conditions, on hard road surfaces.



Dynamic Stability Control (DSC) must be switched off when using traction devices. DSC limits wheel spin which is required to maintain traction in deep snow conditions.



Do not exceed 50 km/h (30 mph) when traction devices are fitted.



Do not fit traction devices to a temporary spare wheel.

Land Rover approved traction devices may be used to improve traction on a hard road surface in heavy snow conditions. They should not be used in off-road conditions.

If it is necessary to fit traction devices, the following points should be observed:

- Single sided Spike-spyder traction devices can only be fitted to the front wheels of vehicle fitted with 18 or 19 inch diameter wheels.
- The wheels and tyres fitted must conform to the specifications of the original equipment.
- No traction devices should be fitted to the rear wheels.
- Only Land Rover approved traction devices should be used on the vehicle. Only Land Rover approved traction devices have been tested to ensure that they do not cause damage to the vehicle. Contact your Dealer/Authorised Repairer for information.
- Always read, understand, and follow the snow chain manufacturer's instructions. Pay particular attention to the maximum speed and fitting instructions.
- Avoid tyre/vehicle damage by removing the traction devices as soon as the conditions allow.