

2012 MY Maintenance Schedule Range Rover Sport

NOTE: The maintenance intervals listed are for vehicles operating under normal driving, road, and climatic conditions. More frequent attention may be necessary if the vehicle is subject to routine stop & go driving, extreme temperatures, dusty conditions, off-road driving, or frequent trailer towing. Consult your Land Rover Retailer for more information.

		Maintenance Interval – whichever occurs first (based on expected vehicle display).												
SERVICE		Miles x 1000	15	30	45	60	75	90	105	120	135	150		
		Months	12	24	36	48	60	72	84	96	108	120		
Kilometers x 1000														
		Miles x 1000	15	30	45	60	75	90	105	120	135	150		
		Months	12	24	36	48	60	72	84	96	108	120		
		Kilometers x 1000	24	48	72	96	120	144	168	192	216	240		
VEHICLE INTERIOR														
Change engine oil and replace filter		●	●	●	●	●	●	●	●	●	●	●		
Reset the Service Interval Indicator		●	●	●	●	●	●	●	●	●	●	●		
Reset engine oil level indicator		●	●	●	●	●	●	●	●	●	●	●		
Check operation of all lights, warning indicators and horn		●	●	●	●	●	●	●	●	●	●	●		
Check operation of front/rear wiper washer systems		●	●	●	●	●	●	●	●	●	●	●		
Check condition and security of seats and seat belts		●	●	●	●	●	●	●	●	●	●	●		
Replace pollen filter		●	●	●	●	●	●	●	●	●	●	●		
VEHICLE EXTERIOR														
Check condition of wiper blades		●	●	●	●	●	●	●	●	●	●	●		
Check operation of all door checks, hood latch, and fuel flap: lubricate door checks		●	●	●	●	●	●	●	●	●	●	●		
ENGINE COMPARTMENT														
Check battery condition; Check / top up electrolyte level		●	●	●	●	●	●	●	●	●	●	●		
Check / top up fluid levels (brake, power steering, windshield washer)		●	●	●	●	●	●	●	●	●	●	●		
Check / top up coolant level; check specific gravity		●	●	●	●	●	●	●	●	●	●	●		
Check condition of accessory drive belt(s) and, if fitted, supercharger drive belt		●	●	●	●	●	●	●	●	●	●	●		
Change brake fluid: every 3 years														
Change engine coolant: every 10 years														
Clean debris from auxiliary oil cooler (supercharged vehicles)														
Replace spark plugs														
Replace air cleaner elements; naturally aspirated vehicles														
Replace air cleaner elements; supercharged vehicles														

2012 MY Maintenance Schedule Range Rover Sport

		Maintenance interval – whichever occurs first (based on expected vehicle display).											
SERVICE	Miles x 1000	15	30	45	60	75	90	105	120	135	150		
	Months	12	24	36	48	60	72	84	96	108	120		
	Kilometers x 1000	24	48	72	96	120	144	168	192	216	240		
ENGINE COMPARTMENT (CONTINUED)													
Replace accessory drive belt(s)													
Replace supercharger drive belt (supercharged vehicles); every 7 years													
VEHICLE UNDERBODY													
NOTE: Remove all road wheels before inspecting brake components.													
Inspect brake pads for wear, calipers for leaks, and discs for condition	●	●	●	●	●	●	●	●	●	●	●		
Check adjustment of electronic parking brake	●	●	●	●	●	●	●	●	●	●	●		
Inspect tire pressures, condition, and tread depth	●	●	●	●	●	●	●	●	●	●	●		
Inspect exhaust system for leaks, security and damage	●	●	●	●	●	●	●	●	●	●	●		
Inspect for fluid leaks	●	●	●	●	●	●	●	●	●	●	●		
Inspect condition of driveshafts, suspension, and steering boots/gaiters	●	●	●	●	●	●	●	●	●	●	●		
Inspect fuel, hydraulic and fluid pipes, hoses and unions	●	●	●	●	●	●	●	●	●	●	●		
Inspect electrical harnesses, routing and connections	●	●	●	●	●	●	●	●	●	●	●		
Lubricate wheel spigot bore with anti-seize compound; install road wheels to opposite side of same axle (except unidirectional tires, which install on same side)					●	●	●	●	●	●	●		
Replace all flexible brake hoses; every 6 years													
Replace fuel filter; every 10 years													
Change transmission fluid and filter; every 10 years													
Change rear locking differential oil													
Change front and rear axle oil (non-locking differential); every 10 years													
Change transfer box oil; replace drain and fill plugs and washers													
Remove debris from between Dynamic Response valve block and chassis													
Replace filter in Dynamic Response valve block; replace lost fluid													
Conduct road test, select LOW range gears and drive the vehicle 3 – 4 vehicle lengths, then reset EGH range gears													
If fault lamps are illuminated, interrogate with IDS and report findings													
Check for any outstanding recalls or Service Actions													
Endorse Service Record													