

NOTE: The maintenance intervals listed are for vehicles operating under normal driving, road, and climatic conditions. More frequent attention may be necessary if the vehicle is subject to routine stop & go driving, extreme temperatures, dusty conditions, off-road driving, or frequent trailer towing. Consult your Land Rover Retailer for more information.

	Maintenance Interval – whichever occurs first (based on expected vehicle display).																			
	7.5	15	22.5	30	37.5	45	52.5	60	67.5	75	82.5	90	97.5	105	112.5	120	127.5	135	142.5	150
Miles x 1000	7.5	15	22.5	30	37.5	45	52.5	60	67.5	75	82.5	90	97.5	105	112.5	120	127.5	135	142.5	150
Months	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102	108	114	120
Kilometers x 1000	12	24	36	48	60	72	84	96	108	120	132	144	156	168	180	192	204	216	228	240
SERVICE	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Change engine oil and replace filter																				
VEHICLE INTERIOR																				
Reset the Service Interval Indicator	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check operation of all lights, warning indicators and horn	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check operation of front/rear wiper washer systems	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check condition and security of seats and seat belts	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Replace pollen filter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
VEHICLE EXTERIOR																				
Check condition of wiper blades	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check operation of all door checks, hood latch, and fuel flap; Lubricate door checks	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ENGINE COMPARTMENT																				
Check battery condition; check / top up electrolyte level	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check / top up fluid levels (brake, power steering, windshield washer)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check / top up coolant level; check specific gravity	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check condition of accessory drive belt(s)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Change brake fluid: every 3 years																				
Change engine coolant: every 10 years																				
Replace spark plugs																				
Replace air cleaner element	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Replace accessory drive belt																				

	Maintenance Interval – whichever occurs first (based on expected vehicle display).																					
	Miles x 1000	7.5	15	22.5	30	37.5	45	52.5	60	67.5	75	82.5	90	97.5	105	112.5	120	127.5	135	142.5	150	
Months	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102	108	114	120		
Kilometers x 1000	12	24	36	48	60	72	84	96	108	120	132	144	156	168	180	192	204	216	228	240		
SERVICE																						
VEHICLE UNDERBODY																						
NOTE: Remove all road wheels before inspecting brake components.																						
Inspect brake pads for wear, calipers for leaks, and discs for condition		•			•			•			•			•			•			•		•
Check operation of parking brake		•			•			•			•			•			•			•		•
Inspect tire pressures, condition, and tread depth		•			•			•			•			•			•			•		•
Inspect exhaust system		•			•			•			•			•			•			•		•
Inspect for fluid leaks		•			•			•			•			•			•			•		•
Inspect condition of driveshafis, suspension, and steering boots/gaiters					•			•			•			•			•			•		•
Inspect fuel, hydraulic and fluid pipes, hoses and unions					•			•			•			•			•			•		•
Inspect electrical harnesses, routing and connections					•			•			•			•			•			•		•
Lubricate wheel spigot bore with anti-seize compound; install road wheels		•			•			•			•			•			•			•		•
Replace all flexible brake hoses: every 6 years																						
Change transmission fluid and filter: every 10 years																						
Change rear differential oil: every 10 years																						
Change transfer box oil: every 10 years																						
Conduct road test		•			•			•			•			•			•			•		•
If fault lamps are illuminated, interrogate with IDS and report findings		•			•			•			•			•			•			•		•
Check for any outstanding Recalls or Service Actions		•			•			•			•			•			•			•		•
Endorse Service Record		•			•			•			•			•			•			•		•