Technical specifications

WEIGHTS

	Vehicle weight from kg (lb)	Gross Vehicle Weight (GVW) ¹ kg (lb)	Gross Train Weight (GTW) ² kg (lb)
4WD	1640 3615)	2350 (5180)	4150 (9150)
2WD	1595 (3515)	2350 (5180)	3850 (8485)

¹ The maximum permissible weight of the vehicle including passengers and load.

Note: For every 1000m increase above sea level, GTW must be reduced by 10%.

Maximum front axle load ¹ kg (lb)	Maximum rear axle load ¹ kg (lb)	Maximum roof rack load ² kg (lb)	Maximum payload ³ kg (lb)
1300(2865)	1145 (2525)	75 (165)	500 (1100)

¹ The front and rear axle maximum loads can not be reached simultaneously as this will exceed the GVW limit.

WHEEL ALIGNMENT DATA (CHINA)

Wheel alignment - front toe	+ 0.22°
Wheel alignment - rear toe	+0.18°
Camber - front	-0.51°
Camber - rear	-1.25°

PEDAL TRAVEL (CHINA)

Both the brake and clutch pedal travel are set at the factory and are non-adjustable.

² The maximum permissible weight of the vehicle and braked trailer including their respective loads.

² This figure includes the weight of the roof rack.

³ Options fitted to vehicle will affect maximum payload.