

# Technical specifications

## WEIGHTS

	Vehicle weight from kg (lb)	Gross Vehicle Weight (GVW) <sup>1</sup> kg (lb)	Gross Train Weight (GTW) <sup>2</sup> kg (lb)
<b>4WD</b>	1640 (3615)	2350 (5180)	4150 (9150)
<b>2WD</b>	1595 (3515)	2350 (5180)	3850 (8485)

<sup>1</sup> The maximum permissible weight of the vehicle including passengers and load.

<sup>2</sup> The maximum permissible weight of the vehicle and braked trailer including their respective loads.

**Note:** For every 1000m increase above sea level, GTW must be reduced by 10%.

Maximum front axle load <sup>1</sup> kg (lb)	Maximum rear axle load <sup>1</sup> kg (lb)	Maximum roof rack load <sup>2</sup> kg (lb)	Maximum payload <sup>3</sup> kg (lb)
1300(2865)	1145 (2525)	75 (165)	500 (1100)

<sup>1</sup> The front and rear axle maximum loads can not be reached simultaneously as this will exceed the GVW limit.

<sup>2</sup> This figure includes the weight of the roof rack.

<sup>3</sup> Options fitted to vehicle will affect maximum payload.

## WHEEL ALIGNMENT DATA (CHINA)

<b>Wheel alignment - front toe</b>	+ 0.22°
<b>Wheel alignment - rear toe</b>	+0.18°
<b>Camber - front</b>	-0.51°
<b>Camber - rear</b>	-1.25°

## PEDAL TRAVEL (CHINA)

Both the brake and clutch pedal travel are set at the factory and are non-adjustable.