
The tailgate programmed position memory will now be restored.

SMART KEY BATTERY REPLACEMENT

When the battery needs replacing, there will be a significant decrease in the effective range and **SMART KEY BATTERY LOW** will be displayed in the message centre.



To replace the battery:

1. Remove the cover by sliding in the directions of the arrows.
2. Use the emergency key blade to separate the Smart Key body.
3. Fit a new and unused CR2032 type battery (available from your Land Rover Dealer/Authorised Repairer), with the positive (+) side upwards.

Note: *Avoid touching the new battery, as moisture/oil from fingers can reduce battery life and corrode the contacts.*

Refit the parts in reverse order, ensuring that they click securely into place.

Battery disposal: Used batteries must be disposed of correctly, as they contain harmful substances. Seek advice on disposal from your Land Rover Dealer/Authorised Repairer) and/or your local authority.

SMART KEY CARE

To prevent accidental operation, which may result in an injury, never leave the Smart Key in the vehicle if children or animals are also left in the vehicle.

Do not expose to extremes of heat, dust, humidity or allow contact with fluids. Do not leave the transmitter exposed to direct sunlight.

The emergency key blade number is recorded on an attached label. Peel off the label and attach it to the designated area In the Service Portfolio, supplied in the literature pack. Keep this safe, but not in the vehicle.

The operational range of the Smart Key will vary considerably depending on atmospheric conditions and interference from other transmitting devices.

Note: *The radio frequency used by the Smart Key may be used by other devices (e.g. medical equipment). This may prevent the Smart Key from operating correctly.*