

ENGINE SPECIFICATIONS

Description	Diesel	Petrol
Number of cylinders	4	4
Displacement	2179cc	1999cc
Firing order	1-3-4-2	1-3-4-2
Compression ratio	15.8:1	10:1

LUBRICANTS AND FLUIDS

Description	Variant	Specification
Engine oil	Diesel with Diesel Particulate Filter (DPF)	5W/30 meeting Ford 934-B specification or Castrol SLX Professional Powerflow C1
	Diesel without Diesel Particulate Filter (DPF)	5W/30 meeting Ford 913-B or 913-C specification or Castrol SLX Professional A5
	Petrol	5W/30 meeting Ford 913-B specification
Gearbox oil	Manual	Castrol BOT350 M3
	Automatic	Nippon AW-1 ATF
Power transfer unit	4WD vehicles	Castrol BOT118+
Haldex coupling	4WD vehicles	STAT OIL SL01-301
Rear differential oil	4WD vehicles	Castrol EPX
Brake/Clutch fluid	All vehicles	Shell DOT4 ESL. If unavailable, a low viscosity, synthetic compatible DOT4 brake fluid that meets ISO 4925 class 6 and Land Rover LRES22BF03 requirements may be used.
Screen wash	All vehicles	Screen wash with frost protection
Coolant	All vehicles	50% mixture of Texaco XLC antifreeze and water.

Land Rover recommends Castrol EDGE Professional:

