

CHECKING THE CLUTCH FLUID LEVEL



Clutch fluid is highly toxic. Keep containers sealed and out of reach of children. If consumption of fluid is suspected, seek medical attention immediately.



If the fluid comes into contact with the eyes or skin, rinse immediately with plenty of water.



Avoid spilling clutch fluid onto a hot engine. The fluid is flammable and a fire may result.

Check with the vehicle on level ground.

If significant topping is required, a leak is indicated. Seek qualified assistance.

TOPPING UP THE CLUTCH FLUID



Always top up with fluid of the correct specification. See **101, LUBRICANTS AND FLUIDS**



Clutch fluid will damage paint surface. Soak up any spillage with an absorbent cloth immediately and wash the area with a mixture of car shampoo and water.



Do not use old or previously used clutch fluid. Clutch fluid absorbs moisture when not in a sealed container. Moisture will adversely affect performance.

1. Clean the cap to prevent any dirt from entering the reservoir.
2. Remove the cap.
3. Top up to approximately 10mm (0.4 in) below the top edge. See **101, LUBRICANTS AND FLUIDS**.
4. Replace the cap.

CHECKING THE BRAKE FLUID LEVEL



Brake fluid is highly toxic. Keep containers sealed and out of reach of children. If consumption of fluid is suspected, seek medical attention immediately.



If the fluid comes into contact with the eyes or skin, rinse immediately with plenty of water.



Avoid spilling brake fluid onto a hot engine. The fluid is flammable and a fire may result.



Do not drive the vehicle if the fluid level falls below the **MIN** mark.

With brake wear the fluid level will fall slightly but must not be allowed to fall below the **MIN** mark.

A substantial drop indicates a leak. Do not drive the vehicle. Seek qualified assistance.



If the quantity of fluid in the brake/clutch reservoir drops below the recommended level, a red warning indicator in the instrument pack will illuminate.

Note: If the warning indicator illuminates while the vehicle is being driven, stop the vehicle as soon as safety permits by gently applying the brakes. Check and top-up the fluid level if necessary.

Check with the vehicle on level ground.