

## ENGINE SPECIFICATIONS

	<b>Diesel 150</b>	<b>Diesel 190</b>	<b>Petrol</b>
Capacity	2 179 cm <sup>3</sup>	2179 cm <sup>3</sup>	1999 cm <sup>3</sup>
Firing order	1-3-4-2	1-3-4-2	1-3-4-2
Compression ratio	15.8:1	15.8:1	10:1
Maximum torque	420 Nm at 1750 rpm	420 Nm at 1750 rpm	317 Nm at 3200 rpm
Number of cylinders	4	4	4
Power output	110 kW (150 PS) at 4000 rpm	140 kW (190 PS) at 3500 rpm	177W (240 PS) at 5500 rpm

## LUBRICANTS AND FLUIDS

<b>Part</b>	<b>Variant</b>	<b>Specification</b>
Engine oil	Petrol vehicles 2.0L	SAE 5W-30 meeting Ford 913-B specification.
	Diesel vehicles 2.2L (with DPF)	SAE 5W-30 meeting Ford 934-B specification.
	Diesel vehicles 2.2L (without DPF)	SAE 5W-30 meeting Ford 913-B or 913-C specification.
Main gearbox oil	Manual transmission	Castrol BOT 350 M3
Main gearbox oil	Automatic transmission	Nippon AW-1
Power Transfer unit	All vehicles	Castrol BOT 118
Haldex coupling	All vehicles	STAT OIL SL01-301
Rear differential oil	All vehicles	Castrol EPX
Power steering fluid	All vehicles	Pentosin CHF202
Brake/Clutch fluid	All vehicles	Shell DOT4 ESL. If unavailable, a low viscosity synthetic compatible DOT4 brake fluid that meets ISO 4925 class 6 and Land Rover LRES22BF03 requirements may be used.
Screen washer	All vehicles	Screen wash with frost protection
Coolant	All vehicles	1:1 mixture of Castrol SF antifreeze and water.