

## Child safety

- Adjust the seat cushion to its highest position. If cushion angle adjustment is possible, adjust it to its lowest position.
- Adjust the seat back to the fully upright position.
- Adjust the seat belt upper anchorage to its lowest position.



**Extreme hazard! Do not use a rearward facing child restraint on a seat protected by an airbag in front of it!**



This symbol, affixed to the end of the fascia on the passenger side, warns against the use of a rear-facing child seat in the front passenger seat, when a front passenger airbag is fitted and operational.

### CHILD SEAT POSITIONING

When installing a child seat in the rear, the front seat must be moved forward and upwards to install any rear-facing child seat.

Care must be taken not to load any part of the child seat when repositioning the front seat. The space available for front seat occupants will be reduced by the installation of any rearward-facing child seat.



**Crash statistics show that children are safest when properly restrained in a child or infant restraint system that is secured in a rear seating position.**

### RECOMMENDED CHILD SEATS

| Child size/age   | Recommended seat            |
|------------------|-----------------------------|
| Groups 0 and 0+  | Britax/Römer Baby Safe Plus |
| Group I          | Britax/Römer Duo Plus       |
| Group II and III | Britax/Römer Kid Plus       |

### CHILD RESTRAINT CHECK LIST

Every time a child travels in the vehicle observe the following:-

- Use appropriate child restraints.
- Carefully follow the restraint system manufacturer's instructions.
- Adjust the harnesses for every child on every trip.
- Ensure that all slack is removed from the adult seat belt.
- Always attach the top tether when installing an ISOFIX seat.
- Always check the security of the child restraint.
- Do not dress a child in bulky clothing, or place any objects/padding between the child and the restraint.
- Regularly check the fit and condition of child restraints. If the fit is poor, or wear/damage is visible replace the restraint immediately.
- Set a good example - always wear your seat belt.



**Child restraint anchorages are designed to withstand only those loads imposed by correctly fitted child restraints. Under no circumstances are they to be used for adult seat belts, harnesses or for attaching other items or equipment to the vehicle.**