

The tire pressures indicated on the tire pressure label are for use in all conditions on the original equipment tires. If a reduced speed rating tire is fitted, the recommended pressures are only suitable for use below 100 mph (160 km/h).

For optimum traction, tires should be run in for at least 100 miles (160 kilometers) on dry roads prior to driving on snow or ice.

Note: *The tire traction is significantly degraded in winter conditions when the tread depth is less than 4mm.*

Note: *Some countries have a higher minimum legal tread depth for winter tires than summer tires.*

Recommended winter tires are identified in the following table.

Land Rover approved winter tire sizes	
17 inch wheels	225/65 R17
	235/65 R17
18 inch wheels	235/60 R18
20 inch wheels	245/45 R20

Use of dedicated winter tires may require a change of wheel size, depending on original choice of wheel. All four wheels must be changed.

If fitted with standard rubber valves, the Tire pressure monitoring system (TPMS) warning lamp will flash for 75 seconds and then remain illuminated. The message center will also display **TIRE PRESSURE MONITORING SYSTEM FAULT**.

When the original wheels and tires are refitted, the vehicle will need to travel a short distance to reset the TPMS and extinguish the warning lamp.

USING SNOW CHAINS

WARNING

Use traction devices only in heavy snow conditions, on hard road surfaces.

WARNING

Never exceed 30 mph (50 km/h) when traction devices are fitted.

WARNING

Never fit traction devices to a temporary use spare wheel.

Land Rover approved traction devices may be used to improve traction on compacted snow in heavy snow conditions. They should not be used in off-road conditions.

If it becomes necessary to fit traction devices where there is no compacted snow, the following points must be observed:

- Only Land Rover approved traction devices should be used on the vehicle. Only Land Rover approved traction devices have been tested to ensure that they do not cause damage to the vehicle. Contact your Land Rover Retailer/Authorized Repairer for information.
- The wheels and tires fitted must conform to the specifications of the original equipment.
- Full chain traction devices can be fitted to the rear wheels of vehicles fitted with 19 and 20 inch diameter wheels.
- Half chain traction devices can be fitted to the rear wheels of vehicles fitted with 21 and 22 inch diameter wheels.
- Fit traction devices in pairs on the same axle.