

NOTICE

After any impact, have the seat belts and pre-tensioners checked and, if necessary, replaced by a Land Rover Retailer/Authorized Repairer.

SEAT BELT CARE

⚠ WARNING

The belt should be replaced if webbing becomes frayed, contaminated or damaged. It is essential to replace the entire assembly after it has been worn in a severe impact even if damage to the assembly is not obvious.

If any damage, wear, cuts, defects, or impaired operation are noted with the seat belts, the vehicle should be taken to a Land Rover Retailer/Authorized Repairer for immediate attention. Do not use the vehicle if the seat belts cannot be operated correctly. Care must be taken to avoid contamination of the webbing with polishes, oils and chemicals, and particularly battery acid. Cleaning may safely be carried out using mild soap and water. Contaminated seat belts may not operate correctly in an impact and cannot be relied upon.

When using seat belts to restrain items other than occupants, take care to ensure that the belts are not damaged, or exposed to sharp edges.

SEAT BELT CHECKS

***Note:** If the vehicle is parked on an incline, the seat belt mechanism may lock. This is a safety feature and the belt should be gently eased out from the upper anchorage.*

The seat belts should be inspected regularly to check for fraying, cuts, wear to the webbing and the condition and security of the mechanism, buckles, adjusters and mounting points.

- With the seat belt fastened, give the webbing near the buckle a quick upward pull. The buckle must remain securely locked.
- With the seat belt unfastened, unreel the seat belt to the limit of its travel. Check that it unreels smoothly with no snatches or snags. Allow the belt to fully retract, again checking for smooth operation.
- Partially unreel the seat belt, then hold the tongue plate and give a quick forward pull. The mechanism must lock and prevent any further unreeling.

⚠ WARNING

If any of the seat belts fail to meet those criteria, immediately contact your Land Rover Retailer/Authorized Repairer.

SEAT BELT WARNING LAMP



If a front seat belt is not fastened when the vehicle is in motion, a chime will sound and the seat belt warning lamp will illuminate.

***Note:** If a heavy object is placed on the front passenger seat, it may activate the seat belt reminder. It is recommended that any objects placed on the front passenger seat are secured using the seat belt.*

⚠ WARNING

Always ensure that objects carried within the vehicle are secured properly.