TOPPING UP THE POWER STEERING FLUID

- Power steering fluid will damage painted surfaces. Soak up any spillage with an absorbent cloth immediately and wash the area with a mixture of car shampoo and water.
- Do not fill the reservoir above the **MAX** mark.
- 1. Clean the filler cap before removing to prevent dirt from entering the reservoir.
- 2. Remove filler cap.
- 3. Using Texaco cold climate PAS fluid, top up the reservoir until the fluid level is between the MIN and MAX marks.
- **4.** Replace filler cap.

CHECKING THE WASHER FLUID LEVEL




Some screen washer products are inflammable, particularly if high or undiluted concentrations are exposed to sparking. Do not allow screen washer fluid to come into contact with naked flames or sources of ignition.



If the vehicle is operated in temperatures below 4°C (40°F), use a washer fluid with frost protection. In cold weather, failure to use a washer fluid with frost protection, could result in impaired vision and increase the risk of a vehicle crash.

Do not use an antifreeze or vinegar/water solution in the washer reservoir - antifreeze will damage painted surfaces, while vinegar can damage the windscreen washer pump.



TOPPING UP THE WASHER FLUID

The washer reservoir supplies both front and rear screen washer jets and headlamp washer jets.

Check and top-up the reservoir level at least every week. Always top-up with screen washer fluid to prevent freezing.

Operate the washer switches periodically to check that the nozzles are clear and properly directed.

- 1. Clean the filler cap before removing to prevent dirt from entering the reservoir.
- 2. Remove filler cap.
- 3. Top-up the reservoir until the fluid is visible in the filler neck.
- 4. Replace filler cap.