#### AWARNING

Do not attempt to fit a LATCH child restraint to the center rear seating position. The anchor bars are not designed to hold a LATCH child restraint in this position. Install only using seat belts (non-LATCH system) and the top tether at this position.

#### AWARNING

If the restraint is not correctly anchored, there is a significant risk of injury to the child in the event of a collision or emergency braking.

#### AWARNING

If removing a head restraint in order to fit a child restraint, always secure the head restraint when storing it.

# INSTALLING TETHER ANCHORAGE CHILD RESTRAINTS

# **AWARNING**

Child restraint anchorages are designed to withstand only those loads imposed by correctly fitted child restraints. Under no circumstances are they to be used for adult seat belts, harnesses or for attaching other items or equipment to the vehicle.

# **AWARNING**

Always follow the child seat or restraint system manufacturer's instructions when fitting tether straps.

# **AWARNING**

When fitting a child seat or restraint system, always pass the tether strap over the top of the seat back and beneath the head restraint.

# AWARNING

If a child seat or restraint system is to be fitted to the center seating position, the center armrest must be in the stowed position (folded into the seat).



Second row seats



Third row seats

# Child safety

Your vehicle is equipped with anchorage points for the second and third row seats. These should be used to attach straps from child seats or restraint systems.

- 1. Install the child restraint securely in one of the rear seating positions.
- 2. Pass the tether strap over the seat back and beneath the head restraint.
- 3. Attach the tether strap hook to the tether anchor point. Ensure that the tether strap hook is facing the correct way (see illustration).
- **4.** Tighten the tether strap according to the child restraint manufacturer's instructions.

**Note:** A tether anchorage is provided for the second row center seat position. Do not use this anchor position with a LATCH anchorage child seat