



The load and speed index ratings on all replacement tyres must be, at least, the same specification as the Original Equipment (OE). If in doubt, consult your Dealer/Authorised Repairer.



Do not rotate tyres around the vehicle.



If the use of tyres not recommended by Land Rover is unavoidable, make sure you read, and fully comply with, the tyre manufacturer's instructions.



If lower speed rated specialist tyres are fitted (for example, winter tyres or off road tyres) then the vehicle must be driven within the speed limitations of the tyres. Consult your Dealer/ Authorised Repairer for further information. In markets that require a tyre's maximum speed label to be fitted, the tyre's maximum speed label should be placed within the driver's field of vision. These labels can be obtained from the tyre dealer.

When the tread has worn down to approximately 2 mm, wear indicators start to appear at the surface of the tread pattern. This produces a continuous band of rubber across the tread, as a visual reminder.

Ideally, tyres should be replaced in sets of 4. If this is not possible, replace the tyres in pairs (both front or both rear). When tyres are replaced, the wheels should always be re-balanced and the alignment checked.

For the correct tyre specification and pressures, see **183, TYRE PRESSURES**.

USING WINTER TYRES

In many countries, legislation exists that requires the use of winter tyres during specified periods of the year.

M+S (mud and snow) tyres have a recognised level of winter performance and need not be replaced. The **M+S** marking, on the tyre sidewall, indicates an 'all season' tyre designed for use all year round, including cold temperatures, snow and ice.



This symbol identifies dedicated winter tyres, which can be fitted if optimum winter traction is required, or the vehicle is to be used in more extreme winter conditions.

Note: *A dedicated winter tyre often has a lower speed rating than the Original Equipment (OE) tyre, and the vehicle must therefore be driven within the speed limitation of the tyre. Consult your Dealer/Authorised Repairer for further information. In markets that require a tyre's maximum speed label to be fitted, the tyre's maximum speed label should be placed within the driver's field of vision. These labels can be obtained from the tyre dealer.*

The tyre pressures indicated on the tyre information label, are for use in all conditions on the OE tyres. If a reduced speed rating tyre is fitted, the recommended pressures are only suitable for use below 160 km/h (100 mph).

For optimum traction, tyres should be run in for at least 160 kilometres (100 miles) on dry roads prior to driving on snow or ice.

Land Rover approved winter tyre sizes*	
17 inch wheels	235/65 R17
18 inch wheels	235/60 R18
19 inch wheels	235/55 R19

Note: **Studded tyres are market dependant. Consult a Dealer/Authorised Repairer.*

Use of dedicated winter tyres may require a change of wheel size, depending on the original choice of wheel. All 4 wheels must be changed.