

LUBRICANTS AND FLUIDS

| Part | Variant | Specification |
|-----------------------|------------------------------------|---|
| Engine oil | Petrol vehicles 2.0L | SAE 5W-30 engine oil meeting specification WSS-M2C913-C or B. |
| | Diesel vehicles 2.2L (with DPF) | SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable 5W-30 engine oils to ACEA C2 specification may be used. |
| | Diesel vehicles 2.2L (without DPF) | SAE 5W-30 engine oil meeting specification WSS-M2C913- C or B. If unavailable 5W-30 engine oils to ACEA A5/B5 specification may be used. |
| Main gearbox oil | Manual transmission | Castrol BOT 350 M3 |
| Main gearbox oil | Automatic transmission | Nippon AW-1 |
| Power Transfer unit | All vehicles | Castrol BOT 118 |
| Haldex coupling | All vehicles | STAT OIL SL01-301 |
| Rear differential oil | All vehicles | Castrol EPX |
| Power steering fluid | All vehicles | Pentosin CHF202 |
| Brake fluid | All vehicles | Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used. |
| Screen wash | All vehicles | Screen wash with frost protection |
| Screen cleaning paste | All vehicles | Land Rover screen cleaning paste DNJ500340 |
| Coolant | All vehicles | 1:1 mixture of Castrol SF antifreeze and water |

Land Rover recommends Castrol EDGE Professional:

