

LUBRICANTS AND FLUIDS

| Description | Variant | Specification |
|--|---|---|
| Engine oil | Diesel with Diesel Particulate Filter (DPF) | SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable 5W-30 engine oils to ACEA C2 specification may be used |
| | Diesel without DPF | SAE 5W-30 engine oil meeting specification WSS-M2C913- C or B. If unavailable 5W-30 engine oils to ACEA A5/B5 specification may be used |
| | Petrol | SAE 5W-30 engine oil meeting specification WSS-M2C913-C or B |
| Gearbox oil | Manual | Castrol BOT350 M3 |
| | Automatic | Shell L12108 |
| Active driveline disconnect hydraulic actuator | 4WD vehicles with Active driveline | Pentosin CHF11S |
| Power transfer unit | 4WD vehicles without Active driveline | Castrol BOT448 |
| | 4WD vehicles with Active driveline | Castrol BOT720 |
| Haldex coupling | 4WD vehicles without Active driveline | STAT OIL SL 12-301 |
| Rear differential oil | 4WD vehicles without Active driveline | Castrol BOT448 |
| | 4WD vehicles with Active driveline | Castrol BOT720 |
| Brake/Clutch fluid | All vehicles | Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used. |
| Screen wash | All vehicles | Screen wash with frost protection |
| Screen cleaning paste | All vehicles | Land Rover screen cleaning paste DNJ500340 |
| Coolant | All vehicles | 50% mixture of Texaco XLC antifreeze and water |



Land Rover recommends: **Castrol EDGE Professional**