LUBRICANTS AND FLUIDS

Description	Variant	Specification
Engine oil	Diesel with Diesel Particulate Filter (DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable 5W-30 engine oils to ACEA C2 specification may be used
	Diesel without DPF	SAE 5W-30 engine oil meeting specification WSS-M2C913- C or B. If unavailable 5W-30 engine oils to ACEA A5/B5 specification may be used
	Petrol	SAE 5W-30 engine oil meeting specification WSS-M2C913-C or B
Gearbox oil	Manual	Castrol BOT350 M3
	Automatic	Shell L12108
Active driveline disconnect hydraulic actuator	4WD vehicles with Active driveline	Pentosin CHF11S
Power transfer unit	4WD vehicles without Active driveline	Castrol BOT448
	4WD vehicles with Active driveline	Castrol BOT720
Haldex coupling	4WD vehicles without Active driveline	STAT OIL SL 12-301
Rear differential oil	4WD vehicles without Active driveline	Castrol BOT448
	4WD vehicles with Active driveline	Castrol BOT720
Brake/Clutch fluid	All vehicles	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Screen wash	All vehicles	Screen wash with frost protection
Screen cleaning paste	All vehicles	Land Rover screen cleaning paste DNJ500340
Coolant	All vehicles	50% mixture of Texaco XLC antifreeze and water



Land Rover recommends: Castrol EDGE Professional