


DIMENSIONS



Item	Description	mm (inches)	Degrees
A	Width (including mirrors)	2 220 (87.4)	-
B	Height (standard road height):	1 780 (70.1)	-
C	Approach angle ¹	-	24.3°
D	Ramp breakover angle (V6 diesel, V6 petrol, and V8 petrol vehicles) ¹	-	141.2°
	Ramp breakover angle (V8 diesel vehicles) ¹	-	140.4°
E	Wheelbase	2 923 (115.1)	-
F	Overall length	4 850 (191)	-
G	Track - front	1 690 (66.5)	-
	Track - rear	1 685 (66.3)	-
H	Departure angle without tow hitch ²	-	24.9°
H	Departure angle with adjustable height tow hitch ¹	-	14.7°
H	Departure angle with electrically deployable tow hitch (stored):	-	24.9°
H	Departure angle with electrically deployable tow hitch (deployed):	-	16.1°
-	Wading depth ³	850 (33.5)	-
-	Minimum ground clearance ⁴	213 (8.4)	-
-	Turning circle (wall to wall)	12 500 (492)	-
¹ At EEC kerb weight and Standard road height.			
² At EEC kerb weight plus full size spare tyre and at Standard road height.			
³ For further information, see WADE SENSING in the Owner's Handbook.			
⁴ With Standard suspension height selected. When driving off-road, vehicle's fitted with deployable side steps, fixed side steps or side tubes, have a different ground and side clearance.			