

ENGINE SPECIFICATIONS

	V6 diesel	V8 diesel	V6 petrol	V8 petrol	V8 petrol S/C
Capacity	2 993 cc	4 367 cc	2 995 cc	4 999 cc	4 999 cc
Firing order	1-4-2-5-3-6	1-5-4-2-6-3-7-8	1-4-2-5-3-6	1-5-4-2-6-3-7-8	1-5-4-2-6-3-7-8
Bore	84.0 mm	84.0 mm	84.5 mm	92.5 mm	92.5 mm
Stroke	90.0 mm	98.5 mm	89 mm	93.0 mm	93.0 mm
Number of cylinders	6	8	6	8	8
Compression ratio	16:1	16.1 ± 0.5:1	10.5:1	11.5:1	9.5:1

PERFORMANCE DATA

China only

Variant	Maximum power (kW) at engine speed (rpm)	Maximum torque (Nm) at engine speed (rpm)	Maximum design power (kW)	Maximum gradient ¹	Maximum vehicle speed (km/h)
V8 petrol	375 at 6 500	625 at 2 500	375	45°	225 250 ²
V6 petrol	250 at 6 500	450 at 3 500	250	45°	210
Diesel	190 at 4 000	600 at 2 000	190	45°	210
¹ At maximum oil level - continuous usage.					
² Vehicles fitted with 22 inch wheels only.					