

## LUBRICANTS AND FLUIDS

Part	Variant	Specification
<b>Engine oil</b>	Diesel vehicles with a Diesel Particulate Filter (DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable, 5W-30 engine oils to ACEA C2 specification may be used.
	Diesel vehicles without a DPF	SAE 5W-30 engine oil meeting specification WSS-M2C913-C. If unavailable, 5W-30 engine oils to ACEA A5/B5 specification may be used.
	V6 petrol vehicles	SAE 5W-20 engine oil meeting specification WSS-M2C925-A. If unavailable or, where ambient temperatures fall to lower than -20° C, SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122 should be used.
	V8 petrol vehicles	SAE 5W-20 engine oil meeting specification WSS-M2C925-A.
<b>Transmission oil</b>	All transmissions	Land Rover recommends Shell ATF L12108.
<b>Transfer gearbox oil</b>	V6 diesel, V8 diesel, V6 petrol and V8 petrol vehicles	Land Rover recommends TL 7300 Shell TF 0753.
<b>Front differential oil</b>	All vehicles	Land Rover recommends Castrol SAF-XO.
<b>Rear differential oil</b>	Non-locking	Land Rover recommends Castrol SAF-XO.
<b>Rear differential oil</b>	Electronic locking	Land Rover recommends Castrol BOT 720.
<b>Dynamic response fluid</b>	V8 diesel and V8 petrol	Land Rover recommends Texaco Cold Climate PAS fluid 33270.
<b>Brake fluid</b>	All vehicles	Use Land Rover brake fluid. If unavailable, for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
<b>Screen wash</b>	All vehicles	Screen wash with frost protection.
<b>Screen cleaning paste</b>	All vehicles	Land Rover screen cleaning paste DNJ500340.
<b>Coolant</b>	All vehicles	Land Rover recommends a 1:1 mixture of Havoline XLC antifreeze and water.

Jaguar Land Rover recommends Castrol oils.

