

LUBRICANTS AND FLUIDS

Part	Specification
Engine oil	SAE 5W-30
Manual gearbox oil	Castrol BOT 130M or equivalent
Transfer gearbox	API GL4 or GL5, MIL-L-2105 or MIL-L-2105B, C or D
Front axle swivel pin housings	Texaco Molytex EP00 or equivalent
Front differential oil	API or GL5, MIL-L-2105 or MIL-L-2105B, C or D
Rear differential oil	API or GL5, MIL-L-2105 or MIL-L-2105B, C or D
Gearbox extension shaft to transfer box	Weicon Anti Seize Standard Grade or equivalent
Wheel hubs	Castrol Optimal Olista Long Time 2 grease or equivalent
Clutch fluid	Shell Donax YB, Shell DOT4 ESL or synthetic compatible fluid meeting FMVSS 116 DOT4 specification
Power steering fluid	Texaco Cold Climate 33270 or equivalent
Brake fluid	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Screen washer	Screen wash with frost protection
Coolant	Use only a 50% mix of water and Texaco XLC or Havoline XLC or equivalent

Land Rover recommends:

