

LUBRICANTS AND FLUIDS

Description	Variant	Specification
Engine oil	Diesel with Diesel Particulate Filter (DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable, 5W-30 engine oils to ACEA C2 specification may be used.
	Diesel without DPF	SAE 5W-30 engine oil meeting specification WSS-M2C913-C. If unavailable, 5W-30 engine oils to ACEA A5/B5 specification may be used.
	Petrol	SAE 5W-30 engine oil meeting specification WSS-M2C913-C.
Gearbox oil	Manual	Land Rover recommends Castrol BOT350 M3.
	Automatic	Land Rover recommends Shell L12108.
Active driveline disconnect hydraulic actuator	4WD vehicles with Active driveline	Land Rover recommends Pentosin CHF11S.
Power transfer unit	4WD vehicles without Active driveline	Land Rover recommends Castrol BOT448.
	4WD vehicles with Active driveline	Land Rover recommends Castrol BOT720.
Haldex coupling	4WD vehicles without Active driveline	Land Rover recommends STAT OIL SL 12-301.
Rear differential oil	4WD vehicles without Active driveline	Land Rover recommends Castrol EPX.
	4WD vehicles with Active driveline	Land Rover recommends Castrol BOT720.
Brake/Clutch fluid	All vehicles	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Screen wash	All vehicles	Screen wash with frost protection.
Screen cleaning paste	All vehicles	Land Rover screen cleaning paste DNJ500340.
Coolant	All vehicles	50% mixture of Texaco XLC antifreeze and water.



Land Rover recommends: **Castrol EDGE Professional**