LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	V6 diesel vehicles with DPF	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable, 5W-30 engine oils to ACEA C2 specification may be used.
	V6 diesel vehicles without DPF	SAE 5W-30 engine oil meeting specification WSS-M2C913- C. If unavailable 5W-30 engine oils to ACEA A5/B5 specification may be used.
	V6 petrol vehicles	SAE 0W-20 engine oil meeting Jaguar Land Rover specification STJLR.51.5122.
Transmission oil	All transmissions	Land Rover recommends Shell ATF L12108.
Transfer gearbox oil	Without low range transmission	Land Rover recommends Castrol BOT 850.
	With low range transmission	Land Rover recommends Shell TF 0753.
Front differential oil	All vehicles	Land Rover recommends Castrol SAF-XO.
Rear differential oil	Non-locking	Land Rover recommendsCastrol SAF-XO.
Rear differential oil	Electronic Locking	Land Rover recommends Castrol SAF BOT 720.
Power steering fluid	All vehicles	Land Rover recommends Texaco Cold Climate PAS fluid 33270.
Brake fluid	All vehicles	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Screen washer	All vehicles	Screen wash with frost protection.
Coolant	All vehicles	Land Rover recommends a 1:1 mixture of Havoline XLC antifreeze and water.

Jaguar Land Rover recommends Castrol oils:

