LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	Petrol vehicles 2.0L	SAE 5W-30 engine oil meeting specification WSS-M2C913-C.
	Diesel vehicles 2.2L (with DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable 5W-30 engine oils to ACEA C2 specification may be used.
	Diesel vehicles 2.2L (without DPF)	SAE 5W-30 engine oil meeting specification WSS-M2C913-C. If unavailable 5W-30 engine oils to ACEA A5/B5 specification may be used.
Main gearbox oil	Manual transmission	Land Rover recommends Castrol BOT 350 M3.
Main gearbox oil	Automatic transmission	Land Rover recommends Nippon AW-1 ATF.
Power Transfer unit	All vehicles	Land Rover recommends Castrol BOT 118+.
Haldex coupling	All vehicles	Land Rover recommends STAT OIL SL01-301.
Rear differential oil	All vehicles	Land Rover recommends Castrol EPX.
Power steering fluid	All vehicles	Land Rover recommends Pentosin CHF202.
Brake fluid	All vehicles	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Screen wash	All vehicles	Screen wash with frost protection.
Screen cleaning paste	All vehicles	Land Rover screen cleaning paste DNJ500340.
Coolant	All vehicles	Land Rover recommends 1:1 mixture of Texaco XLC and water.

Land Rover recommends Castrol EDGE Professional: