SAFETY PRECAUTIONS

- Avoid exposing the fuel gases to any potential sources of ignition as the resulting fire and explosion may cause serious injuries and/or death.
- Switch off the engine when refuelling, as it is both a source of extreme temperatures, and electrical sparks.



Switch off any personal electronic devices such as mobile phones or music players.

- Do not operate the auxiliary heater when refuelling the vehicle. Doing so may cause fuel vapours to combust causing a fire/explosion.
- Do not operate the auxiliary heater while the vehicle is in an enclosed space. Doing so can cause a build up of highly toxic fumes which may cause unconsciousness or death.

PETROL ENGINED VEHICLES

- Use high quality fuel that meets the specification defined by EN228 (or the national equivalent)
- Do not use leaded fuels, fuels with lead substitutes (e.g. manganese-based), or fuel additives, as these may adversely affect the emissions control systems, and may affect warranty coverage.

OCTANE RATING

Jaguar Land Rover requires the use of premium unleaded fuel with a minimum octane rating of 95 RON (Research Octane Number) to contribute to optimum performance, fuel economy and driveability. If premium unleaded fuel is not available, you may use unleaded fuel with a lower octane rating, down to a minimum of 91 RON, but this may reduce engine performance, increase fuel consumption, cause audible engine 'knock' and other driveability problems.



CAUTION: Do not use fuels with an octane rating lower than 91 RON as severe engine damage may occur.

If a heavy persistent engine knock is detected, even when using fuel to the recommended octane rating, or if you hear engine knock while holding a steady speed on level roads, consult your Dealer/Authorised Repairer to have the problem corrected. Failure to do so is misuse of the vehicle, for which Jaguar Land Rover is not responsible.

ETHANOL

Fuels containing up to 10% ethanol (E5 & E10) may be used.

- This vehicle is not suitable for use with fuels containing more than 10% ethanol.
- ()

Do not use E85 fuels (85% ethanol content) as serious engine and fuel system damage will occur.

METHANOL

1

Wherever possible, avoid using fuel containing methanol.

Use of fuels containing methanol may cause serious engine and fuel system damage, which may not be covered under warranty.