
## LIGHTING CONTROL







E160313

 With the headlamps on, push the control away from the steering wheel to select high beam. The Instrument panel warning lamp will illuminate. See 50, HIGH BEAM (BLUE).

Nate: Do not use high beam where it may

**Note:** Do not use high beam where it may distract other road users.

- 2. Pull the control towards the steering wheel and release to flash the high beam on and off. The high beam will remain on for as long as the switch is held.
- Side lamps: Rotate the control to this position to switch the side lamps on. The Instrument panel warning lamp will illuminate. See 49, SIDE LAMPS (GREEN).
- **4.** Headlamps: Rotate the control to this position to switch the headlamps on.
- 5. AUTO: With Auto lamps selected, when the ambient light fades and the ignition is on, the side lamps, tail lamps, dipped beam headlamps and licence plate lamps will switch on automatically. Headlamp courtesy delay, High beam assist and the Windscreen wipers detection may also be activated.

**Note:** Low exterior light levels, caused by adverse weather conditions, may also cause the Auto lamps to activate.

6. Front fog lamps: Will operate only while side lamps, headlamps or Auto lamps are selected. Rotate the collar away from the steering wheel and release. The Instrument panel warning lamp will illuminate. See 49, FRONT FOG LAMPS (GREEN).

To turn off the Front fog lamps, rotate the collar away from the steering wheel again and release. The warning lamp will extinguish.

 Rear fog lamps: Will operate only while side lamps, headlamps or Auto lamps are selected. Rotate the collar towards the steering wheel and release. The Instrument panel warning lamp will illuminate. See 48, REAR FOG LAMP (AMBER).

To turn off the Rear fog lamps, rotate the collar towards the steering wheel again and release. The warning lamp will extinguish.