



E132397

This symbol is fixed to the end of the fascia on the passenger side.



E145193

This symbol is fixed to the passenger side sun-visor.

If it is essential that a child travels in the front passenger seat (and national legislation permits this), Land Rover recommends that the following preparations are made before fitting the child restraint:

- Disable the front passenger airbag.
- Adjust the front passenger seat fully rearwards.
- Adjust the lumbar support to its minimum support position.
- Adjust the seat cushion to its highest position. If cushion rake adjustment is possible, adjust it to its lowest position.
- Adjust the seatback to the upright position to support the child restraint.
- Adjust the seat belt adjustable upper anchorage to its lowest position.

## CHILD RESTRAINT CHECK LIST

Every time a child travels in the vehicle, observe the following:

- Carefully follow the instructions provided by the manufacturer of the restraint system.
- Always use the appropriate child restraints and adjust the harnesses for every child, every journey.
- Adjust the harnesses for every child on every journey.
- Make sure that all slack is removed from the vehicle's seat belt.
- Always attach the top tether when installing an ISOFIX seat.
- Always check the security of the child restraint.
- Do not dress a child in bulky clothing or place any objects/padding between the child and the restraint.
- Regularly check the fit and condition of child restraints. If the fit is poor or wear/damage is visible, replace the restraint immediately.
- Set a good example - always wear your seat belt.
- On child seats fitted with a support leg, adjust the leg so that it rests firmly onto the floor.
- For some child seats, it may be necessary to remove the head restraint to ensure a stable fit. Always refit a removed head restraint after the child seat is removed. See **24, HEAD RESTRAINT REMOVAL.**



**WARNING: Child restraint anchorages are designed to withstand only those loads imposed by correctly fitted child restraints. Under no circumstances are they to be used for adult seat belts, harnesses, or for attaching other items or equipment to the vehicle.**