

## ISOFIX child seat positions

Mass group as shown on child restraint	Size classes	Fixtures	Rear outboard seats
<b>Carrycot</b>	F/G	ISO L1/L2	X
<b>0 = Up to 10 kg (22 lb) 0-9 months</b>	E	ISO R1	IL *
<b>0+ = Up to 13 kg (29 lb) 0-18 months</b>	C/D/E	ISO R1/R2/R3	IL *
<b>I = 9 to 18 kg (20 to 40 lb) 9 months - 4 years</b>	C/D A/B1/B	ISO R2/R3 ISO F2/F2X/F3	X IUF
<b>II = 15 to 25 kg (33 to 55 lb) 4-9 years</b>	N/A	N/A	N/A
<b>III = 22 to 36 kg (49 to 80 lb) 8-12 years</b>	N/A	N/A	N/A

- IUF = Suitable for ISOFIX forward child restraint systems of universal category, approved for use in the mass group.
- IL = These ISOFIX child restraint systems are of the specific vehicle, restricted or semi-universal categories.
- X = Not suitable for ISOFIX child restraint fitment in this mass group.
- \* = Child seat suitable for use in these locations, is the Britax/Römer Baby Safe Plus ISOFIX.

**Note:** Ages given are approximate. In case of doubt, the child's weight, not age, should be used when considering an appropriate child seat.

**Note:** The information contained in the table may not be applicable to all countries. If you are in any doubt regarding the type and fitment of child seats, seek advice from a Dealer/Authorised Repairer.

**Note:** ISOFIX anchorages are provided for the rear, second row outer seating positions. ISOFIX child restraints should be securely attached following the manufacturer's instructions at these locations only.

**Note:** A tether anchorage is provided for the rear, second row centre seat position. Do not use this anchor position with an ISOFIX child seat.

## INSTALLING TETHER ANCHORAGE CHILD RESTRAINTS



**WARNING:** Child restraint anchorages are designed to withstand only those loads imposed by correctly fitted child restraints. Under no circumstances are they to be used for adult seat belts, harnesses, or for attaching other items or equipment to the vehicle.



Always follow the child seat or restraint system manufacturer's instructions when fitting tether straps.



When fitting a child seat or restraint system, always pass the tether strap over the top of the seatback and beneath the head restraint.



If a child seat or restraint system is to be fitted to the centre seating position, the centre armrest must be in the stowed position (folded into the seat).