

Technical specifications

LUBRICANTS AND FLUIDS

Description	Variant	Specification
Engine oil	Diesel with DPF (Diesel Particulate Filter)	SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable, 5W-30 engine oils to ACEA C2 specification may be used.
	Diesel without DPF	SAE 5W-30 engine oil meeting specification WSS-M2C913- C. If unavailable, 5W-30 engine oils to ACEA A5/B5 specification may be used.
	Petrol	SAE 5W-30 engine oil meeting specification WSS-M2C913-C.
Gearbox oil	Manual	Land Rover recommends Castrol ECO MTF FE 75W.
	Automatic	Land Rover recommends Shell AFT L12108.
Active driveline disconnect hydraulic actuator	Vehicles with active driveline	Land Rover recommends Pentosin CHF11S.
Power transfer unit	Vehicles without active driveline	Land Rover recommends Castrol BOT448.
	Vehicles with active driveline	Land Rover recommends Castrol BOT720.
Haldex coupling	Vehicles without active driveline	Land Rover recommends Statoil SL 12 301.
Rear differential oil	Vehicles without active driveline	Land Rover recommends Castrol BOT448.
	Vehicles with active driveline	Land Rover recommends Castrol BOT720.
Brake/Clutch fluid	All vehicles	Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used.
Screen wash	All vehicles	Screen wash with frost protection.
Screen cleaning paste	All vehicles	Land Rover screen cleaning paste DNJ500340.
Coolant	All vehicles	50/50 mixture of antifreeze and water - Land Rover recommends Texaco XLC.

Land Rover recommends: **Castrol EDGE Professional**

