

Technical specifications

LUBRICANTS AND FLUIDS

| Description | Variant | Specification |
|--|---|---|
| Engine oil | Diesel with DPF (Diesel Particulate Filter) | SAE 5W-30 engine oil meeting specification WSS-M2C934-B. If unavailable, 5W-30 engine oils to ACEA C2 specification may be used. |
| | Diesel without DPF | SAE 5W-30 engine oil meeting specification WSS-M2C913- C. If unavailable, 5W-30 engine oils to ACEA A5/B5 specification may be used. |
| | Petrol | SAE 5W-30 engine oil meeting specification WSS-M2C913-C. |
| Gearbox oil | Manual | Land Rover recommends Castrol ECO MTF FE 75W. |
| | Automatic | Land Rover recommends Shell AFT L12108. |
| Active driveline disconnect hydraulic actuator | Vehicles with active driveline | Land Rover recommends Pentosin CHF11S. |
| Power transfer unit | Vehicles without active driveline | Land Rover recommends Castrol BOT448. |
| | Vehicles with active driveline | Land Rover recommends Castrol BOT720. |
| Haldex coupling | Vehicles without active driveline | Land Rover recommends Statoil SL 12 301. |
| Rear differential oil | Vehicles without active driveline | Land Rover recommends Castrol BOT448. |
| | Vehicles with active driveline | Land Rover recommends Castrol BOT720. |
| Brake/Clutch fluid | All vehicles | Use Land Rover brake fluid. If unavailable for topping up, a Low Viscosity, DOT4 brake fluid that meets the requirements of ISO 4925 class 6 may be used. |
| Screen wash | All vehicles | Screen wash with frost protection. |
| Screen cleaning paste | All vehicles | Land Rover screen cleaning paste DNJ500340. |
| Coolant | All vehicles | 50/50 mixture of antifreeze and water - Land Rover recommends Texaco XLC. |

Land Rover recommends: **Castrol EDGE Professional**

