IUF = Suitable for ISOFIX forward child restraint systems of universal category, approved for use in the mass group.

IL = These ISOFIX child restraint systems are of the specific vehicle, restricted or semi-universal categories.

X = Not suitable for ISOFIX child restraint fitment in this mass group.

\*For vehicles fitted with sliding second row seats:

- Adjust the seatback to the upright position.
- Adjust the seat to the rear most position, unless the third row seats are occupied.

**Note:** ISOFIX anchorages are provided for second row outer seating positions. ISOFIX child restraints should be securely attached, following the manufacturer's instructions at these locations only.

## **RECOMMENDED CHILD SEATS**

Child size/age	Recommended seat
Groups 0 and 0+	Britax/Römer Baby-Safe plus with Baby-Safe ISOFIX Base
Group I	Britax/Römer Duo Plus
Group II and III	Britax/Römer Kid Plus

## CHILD RESTRAINT CHECK LIST

Every time a child travels in the vehicle observe the following:

- Use appropriate child restraints.
- Carefully follow the restraint system manufacturer's instructions.
- Adjust the harnesses for every child on every journey.
- Make sure all slack is removed from the adult seat belt.

- Always attach the top tether when installing an ISOFIX seat (if applicable to seat type).
- If a head restraint interferes with the fitting of a child restraint, remove the head restraint and stow it securely. See 29, REAR HEAD RESTRAINTS.

Always refit the head restraint when the child seat is removed.

- Always check the security of the child restraint.
- For child seats fitted with a support leg, adjust the leg so that it rests firmly on the floor.
- Do not dress a child in bulky clothing, or place any objects/padding between the child and the restraint.
- Regularly check the fit and condition of child restraints. If the fit is poor, or wear/damage is visible renew the restraint immediately.
- Set a good example always wear your seat belt.
- Make sure that any belt positioning sliders on the seat belts are adjusted such that there is no slack in the lap belt after fastening.

## **BOOSTER SEATS**

In a situation where a child is too large to fit into a child safety seat but is still too small to safely use just the 3-point belt, a booster seat is recommended for maximum safety. Follow the manufacturer's instructions for fitting and use, then adjust the seat belt to suit.

## INSTALLING ISOFIX CHILD RESTRAINTS



Do not attempt to fit ISOFIX restraints to the centre rear seating position. The anchor bars are not designed to hold an ISOFIX restraint in this position.