

LUBRICANTS AND FLUIDS

Part	Variant	Specification
Engine oil	V6 Diesel vehicles	SAE 5W-30 meeting Jaguar Land Rover specification STJLR.03.5005, or WSS-M2C934-B. If unavailable, SAE 5W-30 meeting specification ACEA C2 may be used.
	V8 Diesel vehicles with a Diesel Particulate Filter (DPF)	SAE 5W-30 meeting Jaguar Land Rover specification STJLR.03.5005, or WSS-M2C934-B. If unavailable, SAE 5W-30 meeting specification ACEA C2 may be used.
	V8 Diesel vehicles without a DPF	SAE 5W-30 meeting Jaguar Land Rover specification STJLR.03.5003, or WSS-M2C913-C. If unavailable, SAE 5W-30 meeting specification ACEA A5/B5 may be used.
	Petrol vehicles	SAE 0W-20 meeting Jaguar Land Rover specification STJLR.51.5122.
Diesel exhaust fluid	Diesel vehicles with DEF	Meeting ISO standard 22241-1. Diesel exhaust fluid is also known as DEF, AdBlue, AUS 32 and ARLA 32.
Dynamic response fluid	V8 Diesel and V8 Petrol vehicles	Texaco Cold Climate PAS fluid 33270.
Brake fluid	All vehicles	It is recommended to use Land Rover brake fluid. If unavailable, then brake fluid meeting specification DOT4 ISO 4925 Class 6 may be used.
Windscreen washer fluid	All vehicles	Screen wash with frost protection.
Coolant fluid	All vehicles	Mixture of 50% water and 50% Havoline XLC anti-freeze, meeting Jaguar Land Rover specification STJLR.651.5003.
If in doubt about the required specification of a lubricant or fluid, seek advice from a Retailer/Authorised Repairer.		



E176576

Castrol EDGE Professional exclusively recommended by Land Rover.