

- To open the blind: Press lightly at the rear of the switch and release.
- To close the blind: Press lightly at the front of the switch and release.
- For one-touch open and close operation, press firmly at the front or rear of the switch and release.

Note: Long Wheel Base (LWB) vehicles, fitted with standard rear seats, feature an additional roof blind switch. The switch is located on the rear face of the centre console.

4. Panoramic roof switch:



Wherever possible, remove any snow, ice, dirt, and leaves, etc., from the panoramic roof mechanism, before closing. Failure to do so, may damage the panoramic roof mechanism.



To prevent accidental damage, make sure that any roof rack load will not interfere with the opening of the panoramic roof.

- Press lightly at the rear of the switch to tilt the roof. Once tilted, lightly press again to open the roof.
- From the fully open position, press lightly at the front of the switch to close to the tilt position, then press lightly again to close fully.
- For one-touch open and close operation, press firmly at the front or rear of the switch and release.

Note: The panoramic roof will operate for 40 seconds after the ignition is switched off, provided that a front door is not opened.

ANTI-TRAP PROTECTION



Before closing a window or the panoramic roof, make sure that no occupants have any part of their body in a position where it could be trapped. Even with an Anti-trap system, death or serious injury could occur.

Anti-trap protection will stop window or panoramic roof movement if an obstruction or resistance is detected. Check the window or panoramic roof, and its aperture, and remove any obstructions (e.g., ice, etc.).

If it is still necessary to raise the window or close the panoramic roof, the override procedure is as follows:

1. Attempt to close the window/panoramic roof; Anti-trap will prevent closure and lower the window/open the panoramic roof slightly.
2. Within ten seconds, attempt to raise the window/close the panoramic roof again; Anti-trap will prevent closure and lower the window/open the panoramic roof slightly.
3. Attempt to close the window/panoramic roof for a third time. This time hold the switch in the close position. Hold until closed.

Note: If this procedure fails to remove the blockage, the window operation may need to be reset. See **264, WINDOW RESET**.

Note: The panoramic roof's Anti-trap mechanism works differently and does not require reset if activated. See **264, SUNROOF RESET**.