

These tyres have limited off-road and winter performance, and where conditions dictate should be replaced with the standard all terrain 275/40 R22 108Y or 275/45 R21 110Y M&S tyres or approved winter tyres.

Note: 275/40 R22 108Y tyres must not be fitted to 7 seat derivatives.

Ultra high performance summer tyres (SVR vehicles only)

Your vehicle may be equipped with the optional high performance 295/40 R22 112Y summer tyres, which offer improved on-road performance.

These tyres have limited off-road and winter performance, and where conditions dictate should be replaced with the standard all terrain 275/45 R21 110W M&S tyres or an approved winter tyre.

 **These summer tyres are only approved for fitment to the specified optional fit vehicle derivative, and must not be fitted to vehicles without Active Roll Control (ARC). Do not fit these tyres, in any combination, with other 22" standard all terrain M&S marked tyres or winter tyres.**

USING SNOW CHAINS

 **Only use traction devices in heavy snow conditions, on compacted snow.**

 **Never exceed 50 km/h (30 mph) when traction devices are fitted.**

 **Never fit traction devices to a temporary-use spare wheel.**

Traction devices approved by the vehicle manufacturer, may be used to improve traction in heavy snow conditions, on compacted snow. They should not be used in off-road conditions where there is no compacted snow.

If it becomes necessary to fit traction devices, the following points must be observed:

- Only vehicle manufacturer approved traction devices should be used on the vehicle. Only vehicle manufacturer approved traction devices have been tested to make sure they do not cause damage to the vehicle. Contact your Retailer/Authorised Repairer for information.
- The wheels and tyres fitted must conform to the specifications of the original equipment.
- Full chain traction devices can be fitted to the rear wheels of vehicles fitted with 19 and 20 inch diameter wheels.
- Half chain traction devices can be fitted to the rear wheels of vehicles fitted with 21 and 22 inch diameter wheels.
- Fit traction devices in pairs on the same axle.
- Always read, understand and follow the traction device manufacturer's instructions. Pay particular attention to the maximum speed and fitting instructions.
- Avoid tyre/vehicle damage, by removing the traction devices as soon as the conditions allow.