

-  Only use new fluid from an airtight container (fluid from opened containers, or fluid previously bled from the system will have absorbed moisture, which will adversely affect performance, and must not be used).
- 1. Clean the filler cap before removing, to prevent dirt from entering the reservoir.
- 2. Remove the filler cap.
- 3. Top up the reservoir to the **MAX** mark using the approved brake fluid. See **330, LUBRICANTS AND FLUIDS**.
- 4. Replace the cap and reservoir cover.

CHECKING THE WASHER FLUID LEVEL

-  **Do not allow the screen washer fluid to come into contact with naked flames or sources of ignition.**
-  **If the vehicle is operated in temperatures below 4°C, use a washer fluid with frost protection.**
-  Only use approved washer fluid.
-  Take care to avoid spillage, particularly if an undiluted or high concentration is being used. If spillage occurs, wash the affected area immediately with water.

The washer fluid reservoir supplies the front and rear screen washer jets and the headlamp washer jets.

Check and top up the reservoir level at least every week. Always top up with screen washer fluid to prevent freezing.

Operate the washer switches periodically to check that the nozzles are clear and properly directed.

TOPPING UP THE WASHER FLUID

The washer reservoir supplies both the front and rear screen washer jets and the headlamp washer jets.

Check and top up the reservoir level at least every week. Always top up with screen washer fluid to prevent freezing.

Operate the washer switches periodically to check that the nozzles are clear and properly directed.

1. Clean the filler cap before removing, to prevent dirt from entering the reservoir.
2. Remove the filler cap.
3. Top up the reservoir until the fluid is visible in the filler neck.
4. Replace the filler cap.

Cold climate vehicles also feature a supplemental washer reservoir. The same care points, described above, should be applied to vehicles fitted with a supplemental washer reservoir.

Note: *On vehicles fitted with a supplemental washer reservoir, always check and top up the main reservoir first.*

CHECKING THE DYNAMIC RESPONSE FLUID LEVEL

-  **Dynamic response fluid is highly toxic. Keep containers sealed and out of the reach of children. If accidental consumption of fluid is suspected, seek medical attention immediately.**