The seat belts fitted to your vehicle are designed for adults and larger children. For their safety, it is very important for all infants and children under 12 years of age to be restrained in a suitable child safety seat, appropriate to their age and size.

If it is essential that a child travels in the front passenger seat (and national or state legislation permits this), Jaguar Land Rover Limited recommends that the following preparations are made before fitting the child restraint:

- Disable the front passenger airbag. See **49, DISABLING THE PASSENGER AIRBAG**.
- Adjust the front passenger seat fully rearwards.
- Adjust the lumbar support to its minimum support position.
- Adjust the seat cushion to its highest position. If cushion front tilt adjustment is possible, adjust it to its lowest position.
- Adjust the seatback to an upright position to support the child restraint.

Extreme hazard! Do not use a rearward-facing child restraint on a seat protected by an airbag in front of it!

NEVER use a rearward-facing child restraint on a seat protected by an ACTIVE AIRBAG in front of it, DEATH or SERIOUS INJURY to the CHILD can occur.



E132397

This symbol, affixed to the front door B-post on the passenger side, warns against the use of a rearward-facing child seat in the front passenger seat, when a front passenger airbag is fitted and operational.



E145193

This symbol, affixed to the passenger side sun-visor, warns against the use of a rearward-facing child seat in the front passenger seat, when a front passenger airbag is fitted and operational.

CHILD SEAT POSITIONING

Crash statistics show that children are safest when properly restrained in a child or infant restraint system that is secured in a rear seating position.

Seat belts (or suitable child restraints) should be used by all vehicle occupants, for every trip, no matter how short. Failure to do so will greatly increase the risk of death or serious injury in the event of an accident.

Information given within the table is correct at the time of going to press. However, availability of child restraints may change. Please consult your Retailer/ Authorised Repairer for the latest recommendation.

Note: *The information contained in the following tables may not be applicable to all countries. If you are in any doubt regarding the type and fitment of child seats, seek advice from a Retailer/ Authorised Repairer.*

Note: *Ages given are approximate. In case of doubt, the child's weight, not age, should be used when considering an appropriate child seat.*

Note: *The legislation which governs how and where children should be carried when travelling in a vehicle, is subject to change. It is the responsibility of the driver to comply with all regulations in force.*

Seating positions	**Mass group**				
	0 = Up to 10 kg 0-9 months	**0+ = Up to 13 kg 0-18 months**	**I = 9-18 kg 9 months to 4 years**	**II = 15-25 kg 4-9 years**	**III = 22-36 kg 8-12 years**
Front passenger*	**U**	**U**	**U**	**U**	**U**
Second row seats**	**U**	**U**	**U**	**U**	**U**
Third row seats***	**X**	**X**	**X**	**UF**	**UF**

U = Suitable for universal category restraints, approved for this mass group.

X = Not suitable for the use of child restraints of this mass group.

UF = Suitable for universal forward-facing child restraints of this mass group.

* Always make sure the passenger airbag has been disabled before using a child restraint in this seating position. See **49, DISABLING THE PASSENGER AIRBAG**. The front passenger seat should be positioned fully rearward, the seat cushion to its highest position and the seatback adjusted to an upright position to support the child restraint.

** For vehicles fitted with sliding second row seats:

- Adjust the seatback to the upright position.
- Adjust the seat to the rear most position, unless the third row seats are occupied.

*** Adjust the second row seatback to the upright position and move the seat forward, to give sufficient clearance to allow fitment of the third row child restraint.

ISOFIX Child Seat Positioning

Mass group as shown on child restraint	Size class	Fixtures	Second row outboard*	Recommended child restraint system
Carry-cot	F	ISO/L1	**X**	-
	G	ISO/L2	**X**	-
0 Up to 10 kg (0 - 9 months)	E	ISO/R1	**IL**	Britax/Römer Baby-Safe Plus with Baby-Safe ISOFIX Base
0+ Up to 13 kg (0 - 18 months)	E	ISO/R1	**IL**	
	D	ISO/R2	**IL**	-
	C	ISO/R3	**IL**	-
I 9 to 18 kg (9 months - 4 years)	D	ISO/R2	**IL**	-
	C	ISO/R3	**IL**	-
	B	ISO/F2	**IUF**	Britax/Römer Duo Plus
	B1	ISO/F2X	**IUF**	
	A	ISO/F3	**IUF**	
II/III 15 to 36 kg (4 - 9 years)	-	-	-	-

IUF = Suitable for ISOFIX forward child restraint systems of universal category, approved for use in the mass group.

IL = These ISOFIX child restraint systems are of the specific vehicle, restricted or semi-universal categories.

X = Not suitable for ISOFIX child restraint fitment in this mass group.

*For vehicles fitted with sliding second row seats:

- Adjust the seatback to the upright position.
- Adjust the seat to the rear most position, unless the third row seats are occupied.

Note: *ISOFIX anchorages are provided for second row outer seating positions. ISOFIX child restraints should be securely attached, following the manufacturer's instructions at these locations only.*